


Use And Care



NO-FROST REFRIGERATOR-FREEZER



PART NO. 2182590

Table of Contents

A Note to You	2
Refrigerator Safety	3
Parts and Features	4
Before Using Your Refrigerator	5
Cleaning your refrigerator	5
Installing it properly	5
Plugging it in	6
Leveling it	7
Using Your Refrigerator	8
Setting the controls	8
Changing the control settings	9
Removing the drop-in door trim	10
Adjusting the door bins	10
Adjusting the cantilever	
refrigerator shelves	11
Removing the meat drawer	
and cover	11
Removing the crispers and	40
crisper cover	
Removing the freezer shelf	12
Using the optional automatic	12
ice maker	13

Attaching the optional ice maker	
to a water supply	14
Removing the base grille	16
Changing the light bulbs	17
Understanding the sounds	
you may hear	18
Saving energy	18
Reversing the door swing	19
Caring for Your Refrigerator	21
Cleaning your refrigerator	21
Vacation and moving care	22
Power interruptions	23
Food Storage Guide	24
Storing fresh food	24
Storing frozen food	25
Troubleshooting	26
Requesting Assistance or Service	27
Index	28
Warranty	32

A Note to You

Thank you for buying an ESTATE® appliance.

ESTATE appliances give you all the functionality of name brand appliances at a value price. To ensure you enjoy years of trouble-free operation, we developed this Use and Care Guide. It contains valuable information about how to operate and maintain your appliance properly and safely. Please read it carefully. Also, please complete and mail the Ownership Registration Card provided with your appliance. This card helps us notify you about any new information on your appliance.

Please record your model's information.

Whenever you call to request service on your appliance, you need to know your complete model number and serial number. You can find this information on the model and serial number label (see diagram on page 4 for location of label).

Please also record the purchase date of your appliance and your dealer's name, address, and telephone number.

i	

Keep this book and the sales slip together in a safe place for future reference.

Refrigerator Safety

Your safety is important to us.

This guide contains statements under warning symbols. Please pay special attention to these symbols and follow any instructions given. Here is a brief explanation of the use of the warning symbol.



This symbol alerts you to hazards such as fire, electrical shock, or other injuries.

IMPORTANT SAFETY INSTRUCTIONS

AWARNING

To reduce the risk of fire, electrical shock, or injury when using your refrigerator, follow these basic precautions:

- Read all instructions before using the refrigerator.
- Never allow children to operate, play with, or crawl inside the refrigerator.
- Never clean refrigerator parts with flammable fluids. The fumes can create a fire hazard or explosion.

• FOR YOUR SAFETY •

DO NOT STORE OR USE GASOLINE OR OTHER FLAMMABLE VAPORS AND LIQUIDS IN THE VICINITY OF THIS OR ANY OTHER APPLIANCE. THE FUMES CAN CREATE A FIRE HAZARD OR EXPLOSION.

- SAVE THESE INSTRUCTIONS -

Proper disposal of your old refrigerator


AWARNING

Suffocation Hazard Remove doors from your old refrigerator. Failure to do so can result in death or brain damage.

IMPORTANT: Child entrapment and suffocation are not problems of the past. Junked or abandoned refrigerators are still dangerous ... even if they will sit for "just a few days." If you are getting rid of your old refrigerator, please follow the instructions below to help prevent accidents.

BEFORE YOU THROW AWAY YOUR OLD REFRIGERATOR OR FREEZER:


- Take off the doors.
- Leave the shelves in place so that children may not easily climb inside.




Parts And Features

Below are illustrations of your appliance with the parts and features called out. To help you find information on specific parts or features faster, page references are included.

NOTE: The model you purchased may have all or some of the parts and features shown and they may not match the illustrations exactly. This manual covers several models.



Control panel





Before Using Your Refrigerator

It is important to prepare your refrigerator for use. This section tells you how to clean it, install it, connect it to a power source, and level it. For information on how to attach the optional ice maker to a water supply, see page 14, or for information on how to reverse the door swing, see page 19.

Cleaning your refrigerator

Removing packaging materials

Remove tape and any inside labels (except the model and serial number label) before using the refrigerator.

To remove any remaining tape or label glue:

• Rub briskly with thumb.

OR

 Apply liquid hand-dishwashing detergent to area before removing glue as described above. Do not use sharp instruments, rubbing alcohol, flammable fluids, or abrasive cleaners. These can damage the material. See "Important Safety Instructions" on page 3. **NOTE:** Do not remove any permanent instruction labels inside your refrigerator. Do not remove the Tech Sheet fastened under the refrigerator at the front.

Cleaning it before use


After removing all packaging materials,



clean your refrigerator before using it, if necessary. See cleaning instructions on page 21.

Installing it properly

- 1. Allow ½-inch (1.25 cm) space on each side and at the top of the refrigerator for ease of installation.
- 2. If the hinge side of the refrigerator is to be against a wall, you might want to leave extra space so the door can be opened wider.
- **3.** The refrigerator can be flush against the back wall.



BEFORE USING YOUR REFRIGERATOR

Plugging it in

AWARNING



Fire Hazard

Do not use an extension cord.

Doing so can result in death, fire, or electrical shock.


Recommended Grounding Method

A 115 volt, 60 Hz., AC only 15 or 20 ampere fused and properly grounded electrical supply is required. It is recommended that a separate circuit serving only this appliance be provided. Use a receptacle which cannot be turned off with a switch or pull chain. Do not use an extension cord.

AWARNING



Electrical Shock Hazard
Plug into a grounded 3 prong outlet.
Do not remove ground prong.
Do not use an adapter.
Failure to follow these instructions can result in death or electrical shock.



Leveling it

AWARNING




Burn Hazard

Do not touch refrigeration tubes near defrost pan.

Doing so can result in burns.

Your refrigerator has 2 front leveling screws – 1 on the right and 1 on the left. To adjust 1 or both of these, follow the directions below.

- 1. Remove base grille. (See page 16.)
- 2. To raise front, turn screw clockwise.
- **3.** To lower front, turn screw counterclockwise.
- 4. Check with level.
- **5.** Replace base grille. (See page 17.)




Using Your Refrigerator

To obtain the best possible results from your refrigerator, it is important that you operate it properly. This section tells you how to set the controls, remove and adjust some of the features in your refrigerator, and how to save energy.

Setting the controls


Controls for the refrigerator and freezer are in the refrigerator. When you plug in the refrigerator for the first time:

Set the Refrigerator Control to 4
 (Recommended Setting). Refrigerator
 Control settings range from 1 (warmest)
 to 8 (coldest).



- 2. Set the Freezer Control to C (Recommended Setting). Freezer Control settings range from A (warmest) to D (coldest).
- **3.** Give the refrigerator time to cool down completely before adding food. This may take several hours.

The settings indicated above should be correct for normal, household refrigerator usage. The controls are set correctly when milk or juice is as cold as you like and when ice cream is firm. If you need to adjust these settings, see "Changing the control settings" on page 9.



Exterior moisture control

The Exterior Moisture Control operates electric heaters around the door openings. These heaters help keep moisture from forming on the outside of the refrigerator cabinet.

- Use the OFF setting when humidity is low.
- Use the ON setting if moisture forms on the outside of the refrigerator cabinet.





Changing the control settings

If you need to adjust temperatures in the refrigerator or freezer, use the settings listed in the chart below as a guide. If you have questions, call our Consumer Assistance Center telephone number, 1-800-253-1301.

- Adjust the Refrigerator Control first.
- Wait at least 24 hours between adjustments.
- Then adjust the Freezer Control if needed.

CONDITION:	REASON:	RECOMMENDE CONTROL SETT Refrigerator	
Refrigerator section too warm	Door opened oftenLarge amount of food addedRoom temperature too warm	6	A
Freezer section too warm	 Door opened often Large amount of food added Very cold room temperature (can't cycle often enough) 	4	D
Refrigerator section too cold	 Controls not set correctly for your conditions 	2	D
lce not made fast enough	Heavy ice usageVery cold room temperature (can't cycle often enough)	4	D
Both sections too warm	 Door opened often Large amount of food added Very warm or very cold room temperatures 	6	В

Removing the drop-in door trim

(on some models)


To remove the trim piece:

- 1. Remove all items from the shelf.
- 2. Pull straight up on the trim piece at each end.



To replace the trim piece:

- 1. Locate each end of the trim piece above the trim pocket opening.
- 2. Push the trim piece straight down until it stops.
- 3. Replace items on the shelf.




Adjusting the door bins

To remove door bins:

- 1. Lift bin up.
- 2. Pull bin straight out.

To replace door bins:

- 1. Slide bin in above desired support button.
- 2. Push down until it stops.





Adjusting the cantilever refrigerator shelves


Adjust the shelves to match the way you use your refrigerator. Glass shelves are strong enough to hold bottles, milk, and other heavy food items.

To remove a shelf:

- 1. Remove items from shelf.
- 2. Tilt shelf up at front.
- 3. Lift shelf at back.
- 4. Pull shelf straight out.

To replace a shelf:

- Guide the rear shelf hooks into the slots in the shelf supports on the back liner wall.
- Tilt front of shelf up until hooks drop into slots.
- 3. Lower front of shelf to a level position.



NOTE: Glass shelves are heavy. Handle them carefully.

Removing the meat drawer and cover

To remove the meat drawer:


- 1. Slide meat drawer out to the stop.
- 2. Lift front of meat drawer and slide meat drawer out the rest of the way.
- 3. Replace in reverse order.

To adjust the cover position:

- 1. Tilt front of cover up.
- 2. Lift back of cover.
- 3. Pull cover straight out.

To replace the cover:

- 1. Guide the cover's rear hooks into the slots in the shelf supports on cabinet wall.
- Tilt cover up at front until the hooks drop into slots.
- 3. Lower front of cover to a level position.




Pull out to the stop, lift the front, and pull again.

Removing the crispers and crisper cover

To remove the crispers:

- 1. Slide crisper straight out to the stop.
- 2. Lift the front and slide out the rest of the way.
- 3. Replace in reverse order.



Pull out to the stop, lift the front and pull again.

To remove the cover:


- Push up the glass insert from the bottom, then slide out with both hands.
- 2. Lift front of cover frame.
- 3. Lift cover frame up and out.

To replace the cover:

- 1. Fit back of cover frame into notch supports on back wall of refrigerator, then lower the front into place.
- Make sure the front cover metal support is in the notches in the sides of the liner. NOTE: If the support is not positioned properly, the doors may not close all the way.
- Slide back of glass insert into place, then lower front.

Remove the cover insert. Lift the cover front, then the back.

NOTE: Handle glass insert with care. It could be heavy.




Removing the freezer shelf

Remove the freezer shelf for easier cleaning.

To remove the shelf:

- 1. Lift front of shelf slightly.
- 2. Lift back of shelf off supports.
- 3. Replace in reverse order.






Using the optional automatic ice maker

If your refrigerator has an automatic ice maker, or if you plan to add one later, here are a few things you will want to know.

The ON/OFF lever is a wire signal arm.
 DOWN to make ice automatically
 UP to shut off ice maker

IMPORTANT: Do not turn the ice maker ON until it is connected to a water supply. Instructions for water supply hookup are attached to the back of the refrigerator cabinet.

- If you remove the ice bin, raise the signal arm to the OFF position. When you replace the bin, push it all the way in and lower the signal arm to the ON position.
- Good water quality is important for good ice quality. Try to avoid connecting the ice maker to a softened water supply.
 Water softener chemicals (such as salt from a malfunctioning softener) can damage the ice maker mold and lead to poor ice quality. If a softened water supply cannot be avoided, make sure the water softener is operating properly and is well maintained.



Solving common ice maker problems

<u> </u>	
PROBLEM	POSSIBLE CAUSE/SOLUTION
Ice crescents attached at corners	 This is normal. They break apart easily. Shake bin occasion- ally to keep cubes separated.
Ice maker will not operate or ice is not	ON/OFF lever is in the OFF (up) position. Lower lever to the ON (down) position.
made fast enough	 Freezer is not cold enough. Adjust temperature controls and wait 24 hours. (See "Changing the control settings" on page 9.)
Off-taste or odor in ice	 New plumbing connections can cause discolored or off- flavored ice. Discard the first few batches of ice.
	 Cubes are stored too long. Throw them away and make a new supply.
	 Foods in freezer are not wrapped properly. See "Food Storage Guide" on page 25.
	 Freezer and ice bin need to be cleaned. See pages 21 and 22. Water may contain minerals (such as sulfur). A filter may be required to remove them.

Attaching the optional ice maker to a water supply

Read all directions carefully before you begin.





Electrical Shock Hazard Unplug the refrigerator before installing ice maker.

Failure to do so can result in death or electrical shock.

IMPORTANT:

- Use copper tubing only and check for leaks.
- Install ice maker tubing in areas where temperatures are above freezing.

Tools required:

- Standard screwdriver
- 7/16-inch and 1/2-inch open-end wrenches or two adjustable wrenches
- ¼-inch nut driver
- 1/4-inch drill bit
- Hand drill or electric drill (properly grounded)

NOTE: Your appliance dealer has a kit available with a ½-inch saddle-type shut-off valve, a union, and copper tubing. Before purchasing, make sure a saddle-type valve complies with your local plumbing codes. Do not use a piercing-type or ¾-inch saddle valve which reduces water flow and clogs more easily.

Cold water supply

The ice maker water valve contains a flow washer which is used as a water pressure regulator. The ice maker needs to be connected to a cold water line with water pressure limitations of 20-120 psi. If a problem occurs, call your utility company.

IMPORTANT:


- It may take up to 24 hours for your ice maker to begin producing ice.
- If operating the refrigerator before installing the water connection, turn ice maker to the OFF position to prevent operation without water.
- All installations must be in accordance with local plumbing code requirements.

Installation is not warranted by refrigerator or ice maker manufacturer.



Connecting to water line

- Find a ½-inch to 1¼-inch vertical COLD water pipe near the refrigerator.
 NOTE: Horizontal pipe will work, but the following precaution must be taken: Drill on the top side of the pipe, not the bottom. This will help keep water away from the drill. This also keeps normal sediment from collecting in the valve.
- 2. Measure from connection on rear of refrigerator to water pipe. Add 7 feet (2.1 m) to allow for moving refrigerator for cleaning. This is the length of ¼-inch O.D. copper tubing you will need for the job (length from connection to water pipe PLUS 7 feet [2.1 m]). Be sure both ends of copper tubing are cut square.
- Turn OFF main water supply. Turn ON nearest faucet long enough to clear line of water.
- **4.** Using a grounded drill, drill a ¼-inch hole on the cold water pipe you have selected.
- 5. Fasten shut-off valve to cold water pipe with pipe clamp. Be sure outlet end is solidly in the ¼-inch drilled hole in the water pipe and that washer is under the pipe clamp. Tighten packing nut. Tighten the pipe clamp screws carefully and evenly so washer makes a watertight seal. Do not overtighten or you may crush the copper tubing, especially if soft (coiled) copper tubing is used. Now you are ready to connect the copper tubing.
- 6. Slip compression sleeve and compression nut on copper tubing as shown in diagram. Insert end of tubing into outlet end squarely as far as it will go. Screw compression nut onto outlet end with adjustable wrench. Do not overtighten. Turn ON main water supply and flush out tubing until water is clear. Turn OFF shutoff valve on the water pipe. Coil copper tubing.




TO REFRIGERATOR →

* Some models may not feature this second compression nut and sleeve.

Connecting to refrigerator

- Disconnect the tube clamp on the back of the product and insert copper tubing through the clamp as shown at the right. Attach the copper tube to the valve inlet using a compression nut and sleeve as shown. Tighten the compression nut. Do not overtighten. Reattach the tube clamp and tube to the back of the cabinet. Move to step 2.
- 2. Turn shut-off valve ON. CHECK FOR LEAKS. TIGHTEN ANY CONNECTIONS (INCLUDING CONNECTIONS AT THE VALVE) OR NUTS THAT LEAK.
- 3. The ice maker is equipped with a built-in water strainer. If local water conditions require periodic cleaning or a well is your source of water supply, a second water strainer should be installed in the 1/4-inch water line. Obtain a water strainer from your nearest appliance dealer. Install at either tube connection.
- 4. Reconnect electrical supply to refrigerator.




Removing the base grille



To remove the grille:

- 1. Open the refrigerator door.
- 2. Pull base grille forward to release the support tabs from the metal clips.
- 3. Do not remove Tech Sheet fastened behind the grille.



To replace the grille:

- 1. Line up grille support tabs with metal clips.
- 2. Push firmly to snap into place.
- 3. Close the refrigerator door.

See cleaning instructions for defrost pan and condenser coils on page 22.

Changing the light bulbs





Electrical Shock Hazard

Unplug the refrigerator before removing a light bulb.

Failure to do so can result in death or electrical shock.

To change the refrigerator light:


- 1. Unplug the refrigerator.
- 2. Reach behind the Control Panel to remove bulb.
- 3. Replace with a 60-watt appliance bulb.
- 4. Plug in the refrigerator.


аь 0

To replace the freezer light:

- 1. Unplug the refrigerator.
- 2. Grasp the top and bottom of the light shield.
- 3. Squeeze and pull light shield out.
- 4. Replace with a 25-watt appliance bulb.
- 5. Snap light shield into place.
- **6.** Plug in the refrigerator.

NOTE: Not all commercial appliance bulbs will fit your refrigerator. Be sure to replace a bulb with one of the same size and shape.





Understanding the sounds you may hear

Your new refrigerator may make sounds that your old one didn't. Because the sounds are new to you, you might be concerned about them. Don't be. Most of the new sounds are normal. Hard surfaces like the floor, walls, and cabinets can make the sounds seem louder.

The following describes the kinds of sounds that might be new to you, and what may be making them.

Slight hum, soft hiss

You may hear the refrigerator's fan motor and moving air.

Clicking or snapping sounds

The thermostat makes a definite click when the refrigerator stops running. It also makes a sound when the refrigerator starts. The defrost timer will click when the defrost cycle starts.

Water sounds

When the refrigerator stops running, you may hear gurgling in the tubing for a few minutes after it stops. You may also hear defrost water running into the defrost water pan.

Ice maker sounds

- Trickling water
- Thud (clatter of ice)

You may hear buzzing (from the water valve), trickling water and the clatter of ice dumped into the bin.

Running sounds

Your refrigerator has a high-efficiency compressor and motor. It will run longer than older designs. It may even seem to run most of the time.

Saving energy

You can help your refrigerator use less electricity.

- Check door gaskets for a tight seal. Level the cabinet to be sure of a good seal.
- Clean the condenser coils regularly.
- Open the door as few times as possible.
 Think about what you need before you open the door. Get everything out at one time. Keep food organized so you won't have to search for what you want. Close the door as soon as food is removed.
- Go ahead and fill up the refrigerator but don't overcrowd it so air movement is blocked.
- It is a waste of electricity to set the refrigerator and freezer to temperatures colder than they need to be. If ice cream is firm in the freezer and drinks are as cold as your family likes them, that's cold enough.
- Make sure your refrigerator is not next to a heat source such as a range, water heater, furnace, radiator, or in direct sunlight.




Reversing the door swing


5/16-inch hex-head socket wrench, No. 2 Phillips screwdriver, flat-head screwdriver, 1/2-inch open-end wrench.


IMPORTANT INFORMATION:

- Before you begin, turn refrigerator OFF, unplug it, and remove any food from door shelves
- Remove base grille.
- When removing hinges, keep doors closed until ready to lift free from cabinet.
- To remove doors, start at the top hinge and work your way down.
- To replace doors, start at the bottom hinge and work your way up.
- Line up doors so they are centered between the sides of the cabinet **and** parallel with each other.
- Seal all unused openings with screws or plastic plugs. Moisture will enter any openings.
- Door seal may be adjusted by adding or removing shims to the center and bottom hinges.

Reversing the hinges









NOTE:

When replacing the doors, set the door gap at ¹¹/₁₆-inch (17 mm).



USING YOUR REFRIGERATOR

Reversing the handles





5/16-inch HEX HEAD HINGE SCREW



COUNTERSINK SCREW



OVAL SEALING SCREW (USE ON BOTTOM OF DOORS)



HANDLE SCREW



OVAL SEALING SCREW (USE ON TOP OF DOORS)

CALL 1-800-253-1301
WITH QUESTIONS OR COMMENTS

Caring for Your Refrigerator

Your refrigerator is built to give you many years of dependable service. However, there are a few things you can do to help extend its product life. This section tells you how to clean your refrigerator and what to do when going on vacation, moving, or during a power outage.

Cleaning your refrigerator

Both the refrigerator and freezer sections



defrost automatically. However, clean both about once a month to help prevent odors from building up. Wipe up spills right away.

To clean your refrigerator, unplug it, take out all removable parts, and clean the refrigerator according to the following directions.





Burn Hazard

Do not touch refrigeration tubes near defrost pan.

Doing so can result in burns.

PART	WHAT TO USE	HOW TO CLEAN
Removable parts (shelves, crisper, etc.)	Sponge or cloth with mild detergent and warm water	Hand wash and dry thoroughly.
Outside	Sponge, cloth, or paper towel with mild detergent,	Wash outside of cabinet. Do not use abrasive or harsh cleaners. Wine and doubters washing.
warm water, and a good appliance wax (or good auto paste wax)		 Wipe and dry thoroughly. Wax painted metal surfaces at least twice a year. Apply wax with a clean, soft cloth. Waxing painted metal surfaces provides rust protection. Do not wax plastic parts.
Inside walls (allow freezer to warm up so cloth won't stick)	Sponge, soft cloth, or paper towel with baking soda or mild detergent and warm water	 Wash with mixture of warm water and: mild detergent, or baking soda (2 tbs to 1 qt [26 g to .95 L] of water). Wipe and dry thoroughly.
Door liners and gaskets	Sponge, soft cloth, or paper towel with mild detergent and warm water	 Wipe and dry thoroughly. DO NOT USE cleaning waxes, concentrated detergents, bleaches, or cleaners containing petroleum on plastic parts.

continued on the next page

CARING FOR YOUR REFRIGERATOR

PART	WHAT TO USE	HOW TO CLEAN
Plastic parts (covers and panels)	Soft, clean sponge or soft, clean cloth with mild detergent and warm water	Wipe and dry thoroughly. DO NOT USE paper towels, window sprays, scouring cleansers, or flammable fluids. These can scratch or damage material. See "Important Safety Instructions" on page 3.
Defrost pan	Sponge or cloth with mild detergent and warm water	 Remove base grille. (See page 16.) Reach into small opening at right edge and remove the defrost pan. Wash, rinse, and dry thoroughly. Replace defrost pan. Make sure to push it completely into the opening. Replace base grille. (See page 17.)
Condenser coils	Vacuum cleaner with extended narrow attachment	 Remove base grille. (See page 16.) Vacuum coils when dusty or dirty. Coils may need to be cleaned as often as every other month. Replace base grille. (See page 17.)

Vacation and moving care

Short vacations

No need to shut off the refrigerator if you will be away for less than four weeks.

- 1. Use up any perishables.
- 2. Freeze other items.
- If your refrigerator has an automatic ice maker:
 - Raise signal arm to OFF (up) position.
 - Shut off water supply to the ice maker.

Long vacations

If you will be gone a month or more:

- 1. Remove all food from the refrigerator.
- 2. If your refrigerator has an automatic ice maker:
 - Turn off the water supply to the ice maker at least one day ahead of time.
 - When the last load of ice drops, turn off the ice maker. Make sure all ice is dispensed out of the ice maker mechanism.
- 3. Unplug the refrigerator.

- 4. Clean it, rinse well, and dry.
- 5. Tape rubber or wood blocks to the tops of both doors to prop them open far enough for air to get in. This stops odor and mold from building up.

To restart refrigerator, see page 8.

Moving

When you are moving the refrigerator to a new home:

- 1. If your refrigerator has an automatic ice maker:
 - Turn off the water supply to the ice maker at least one day ahead of time.
 - Disconnect the water line.
 - After the last load of ice drops, lift the signal arm to the OFF (up) position.
- 2. Remove all food from the refrigerator.
- 3. Pack all frozen food in dry ice.
- 4. Unplug the refrigerator.
- 5. Clean it thoroughly. Wipe well and dry.



- **6.** Take out all removable parts, wrap them well, and tape them together so they don't shift and rattle.
- 7. Screw in the leveling rollers.
- **8.** Tape the doors shut and tape the power supply cord to the cabinet.

When you get to your new home, put everything back and refer to page 5. Also, if your refrigerator has an automatic ice maker, remember to reconnect the water supply line.

Power interruptions

If electricity goes off, call the power company. Ask how long power will be off.

- 1. If service will be interrupted 24 hours or less, **keep both doors closed.** This helps foods stay frozen.
- 2. If service will be interrupted longer than 24 hours:
 - (a) Remove all frozen food and store in a frozen food locker.

OR

(b) Place 2 lbs. (900 g) of dry ice in freezer for every cubic foot (liter) of freezer space. This will keep food frozen for 2 to 4 days. Wear gloves to protect your hands from dry ice burns.

OR

(c) If neither a food locker or dry ice is available, use or can perishable food at once.

3. A full freezer stays cold longer than a partly filled one. A freezer full of meat stays cold longer than a freezer full of baked goods. If food contains ice crystals, it may be safely refrozen, although the quality and flavor may be affected. If the condition of the food is poor, or if you feel it is unsafe, dispose of it.

Questions?

Call our Consumer Assistance Center telephone number from anywhere in the U.S.A., **1-800-253-1301**.

Food Storage Guide

There is a correct way to package and store refrigerated or frozen food. To keep food fresher, longer, take the time to study these recommended steps.

Storing fresh food

Wrap or store food in the refrigerator in airtight and moisture-proof material. This prevents food odor and taste transfer throughout the refrigerator. For dated products, check code date to ensure freshness.

Leafy vegetables

Remove store wrapping and trim or tear off bruised and discolored areas. Wash in cold water and drain. Place in plastic bag or plastic container and store in crisper.

Vegetables with skins (carrots, peppers)

Store in crisper, plastic bags or plastic container.

Fruit

Wash, let dry and store in refrigerator in plastic bags or crisper. Do not wash or hull berries until they are ready to use. Sort and keep berries in their original container in a crisper, or store in a loosely closed paper bag on a refrigerator shelf.

Eggs

Store without washing in the original carton on interior shelf.

Milk

Wipe milk cartons. For best storage, place milk on interior shelf.

Butter or margarine

Keep opened butter in covered dish or closed compartment. When storing an extra supply, wrap in freezer packaging and freeze.

Cheese

Store in the original wrapping until you are ready to use it. Once opened, rewrap tightly in plastic wrap or aluminum foil.

Leftovers

Cover leftovers with plastic wrap or aluminum foil. Plastic containers with tight lids can also be used.

Meat

Store most meat in original wrapping as long as it is airtight and moisture-proof. Rewrap if necessary. See the following for storage times. When storing meat longer than the times given, freeze the meat.

Chicken	1-2	days
Bacon	5-7	days
Ground beef	1-2	days
Cold cuts	3-5	days
Steaks/roasts	3-5	days
Variety meats	1-2	days
Cured meats 7	'-10	days

NOTE: Use fresh fish and shellfish the same day as purchased.



Storing frozen food

The freezer section is designed for storage of commercially frozen food and for freezing food at home.

NOTE: For further information about preparing food for freezing or food storage times, contact your local Cooperative Extension Service or check a freezer guide or reliable cookbook.

Packaging

The secret to successful freezing is in the packaging. The way you close and seal the package must not allow air or moisture in or out. Packaging done in any other way could cause food odor and taste transfer throughout the refrigerator and drying of frozen food.

Packaging recommended for use:

- · Rigid plastic containers with tight-fitting lids
- Straight-sided canning/freezing jars
- Heavy-duty aluminum foil
- Plastic-coated paper
- Non-permeable plastic wraps (made from a saran film)

Follow package or container instructions for proper freezing methods.

Do not use:

- Bread wrappers
- Non-polyethylene plastic containers
- Containers without tight lids
- Waxed paper
- Wax-coated freezer wrap
- Thin, semi-permeable wrap

The use of these wrappings could cause food odor, taste transfer, and drying of frozen food.

Questions?

Call our Consumer Assistance Center telephone number from anywhere in the U.S.A., 1-800-253-1301.

Troubleshooting

Performance problems often result from little things you can fix without tools. Please read through "Before calling for assistance ..." below before calling for service on your appliance.

Before calling for assistance ...

Listed in this chart are the most common problems consumers run into with their appliances. Please read through this and see if it can solve your problem.

PROBLEM	CHECK THE FOLLOWING
Your refrigera- tor will not	Is the power supply cord firmly plugged into a live circuit with proper voltage?
operate	Has a household fuse or circuit breaker blown/tripped?
	Is the Refrigerator Control set to the OFF position?
The lights do not work	Is the power supply cord firmly plugged into a live circuit with proper voltage?
	Has a household fuse or circuit breaker blown/tripped?
	Is a bulb burned out?
The ice maker does not work	Is the freezer cold enough to make ice? It could take overnight for the freezer to reach the proper temperature.
	Is the ON/OFF lever in the ON (down) position? (See page 13.)
	Is the water valve turned on?
	Does the water line have a clog or leak?
You hear unfa-	Is something on top of or behind the refrigerator?
miliar sounds or a rattling/ jingling noise	Some new sounds are normal. See "Understanding the sounds you may hear" on page 18.
There is water in the defrost pan	This is normal on hot, muggy days. Make sure the refrigerator is level so the pan does not overflow.
The motor	Are the condenser coils dirty?
seems to run too much	Has the door been opened often? Has a large amount of food been added at one time? The motor naturally runs longer if these things happen.
	Is the room hot? If the room is too warm, the motor runs longer to keep the unit cool.



Requesting Assistance or Service

For assistance or service:

Before calling for assistance or service, please check "Troubleshooting" on page 26. If may save you the cost of a service call. If you still need help, follow the instructions below.

1. If you need assistance* ...

Call Whirlpool Consumer Assistance



Center telephone number.
Dial toll-free from anywhere in the U.S.A.: 1-800-253-1301 and talk with one of our trained consultants. The consultant

can instruct you in how to obtain satisfactory operation from your appliance or, if service is necessary, recommend a qualified service company in your area.

If you prefer, write to:

Whirlpool Brand Home Appliances Consumer Assistance Center c/o Correspondence Dept. 2000 North M-63 Benton Harbor, MI 49022-2692

Please include a daytime phone number in vour correspondence.

2. If you need service* ...

Whirlpool has a nationwide network of authorized Whirlpool service companies.



Whirlpool service technicians are trained to fulfill the product warranty and provide afterwarranty service, anywhere in the United States. To locate

the authorized Whirlpool service company in your area, call our Consumer Assistance Center telephone number (see Step 1) or look in your telephone directory Yellow Pages under:

•APPLIANCE-HOUSEHOLD-MAJOR, SERVICE & REPAIR

- See: Whirlpool Appliances or Authorized Whirlpool Service (Example: XYZ Service Co.)
- REFRIGERATORS & FREEZERS, SERVICE & REPAIR
- See: Whirlpool Appliances or Authorized Whirlpool Service (Example: XYZ Service Co.)

3. If you need FSP® replacement parts ...

FSP is a registered trademark of Whirlpool Corporation for quality parts. Look for this symbol of quality whenever you need a replacement part for your WHIRLPOOL® appliance. FSP replacement parts will fit right and work right, because they are made to the same exacting specifications used to build every new WHIRLPOOL appliance.

To locate FSP replacement parts in your area, refer to Step 2 or call the Whirlpool Consumer Assistance Center number in Step 1.

4. If you are not satisfied with how the problem was solved ...

- Contact the Major Appliance Consumer Action Program (MACAP). MACAP is a group of independent consumer experts that voices consumer views at the highest levels of the major appliance industry.
- Contact MACAP only when the dealer, authorized servicer, and Whirlpool have failed to resolve your problem.

Major Appliance Consumer Action Program 20 North Wacker Drive Chicago, IL 60606

MACAP will in turn inform us of your action.

* When asking for help or service:

Please provide a detailed description of the problem, your appliance's complete model and serial numbers, and the purchase date. (See page 2.) This information will help us respond properly to your request.

Index

This index is alphabetical. Look for the word or phrase you are interested in, then look for the page number.

TOPIC	PAGE
BASE GRILLE	
Removing	16
CARE	
Moving Power interruptions Vacation	23
CLEANING	5, 21-22
CONTROLS	
Changing settings Setting	9 8
CRISPER	
Cover Removing	12
DOOR TRIM	
Removing	10
ELECTRICAL NEEDS	6
ENERGY	
Saving	18
FEATURES/PARTS	4
FOOD STORAGE	
Fresh	
Erozon	25

TOPIC	PAGE
ICE MAKER	
Common problems Using	13 13
LIGHT BULBS	
Changing	17
PARTS/FEATURES	4
RESPONSIBILITIES	
Owner	3
SAFETY	3
SERVICE	
Parts	
Requesting	27
SHELVES	
Freezer, adjusting	
Refrigerator, adjusting	11
SOUNDS	40
Normal	
TROUBLESHOOTING	26
WARRANTY	32

ESTATE® Refrigerator Warranty

LENGTH OF WARRANTY	WHIRLPOOL WILL PAY FOR
FULL ONE-YEAR WARRANTY From Date of Purchase	FSP® replacement parts and repair labor to correct defects in materials or workmanship. Service must be provided by an authorized Whirlpool service company.
FULL FIVE-YEAR WARRANTY From Date of Purchase	FSP replacement parts and repair labor to correct defects in materials or workmanship in the sealed refrigeration system. These parts are: 1. Compressor 2. Evaporator 3. Condenser 4. Drier 5. Connecting tubing Service must be provided by an authorized Whirlpool service company.

WHIRLPOOL WILL NOT PAY FOR

- A. Service calls to:
 - 1. Correct the installation of your refrigerator.
 - 2. Instruct you how to use your refrigerator.
 - 3. Replace house fuses or correct house wiring or plumbing.
 - 4. Replace light bulbs.
- B. Repairs when your refrigerator is used in other than normal, single-family household use.
- C. Pickup and delivery. Your refrigerator is designed to be repaired in the home.
- **D.** Damage to your refrigerator caused by accident, misuse, fire, flood, acts of God, or use of products not approved by Whirlpool.
- E. Any food loss due to product failure.
- **F.** Repairs to parts or systems caused by unauthorized modifications made to the appliance.

3/96

WHIRLPOOL CORPORATION SHALL NOT BE LIABLE FOR INCIDENTAL OR CONSE-QUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so this exclusion or limitation may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Outside the United States, a different warranty may apply. For details, please contact your authorized Whirlpool dealer.

If you need service, first see the "Troubleshooting" section of this book. After checking "Troubleshooting," additional help can be found by checking the "Requesting Assistance or Service" section, or by calling our Consumer Assistance Center telephone number, 1-800-253-1301, from anywhere in the U.S.A.